



# **Instruction Manual**

# Air Cvlinder

# **55-JCM Series**







(E	$\mathbf{x}$	On a sife. Marking for Explaning Destanting
		Specific Marking for Explosion Protection
		Equipment Group
2		Equipment Category
G	D	Environment (Gas/Dust)
E	x h	Type of Protection - Constructional Safety 'c'
110	С	Gas Sub-Division
111	IC	Dust Sub-Division
Т		Temp. Classification
G	b/Db	Equipment Protection Level
Х		Special Conditions of Use
Ta	а	Ambient Temperature Range
The intended	l use o	f this actuator is to convert the potential energy
	ompres	sed air into a force which causes mechanical linear
motion		

**Note 1:** The X at the end of the certificate number represents that this product is subject to "Special Conditions of Use", please see Section 2.3.

SMC19.0045 X

#### **1 Safety Instructions**

Certifcate Number:

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of "Caution," "Warning" or "Danger." They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC)<sup>-11</sup>, and other safety regulations.

<sup>1)</sup> ISO 4414: Pneumatic fluid power - General rules relating to systems. ISO 4413: Hydraulic fluid power - General rules relating to systems. IEC 60204-1: Safety of machinery - Electrical equipment of machines. (Part 1: General requirements)

ISO 10218-1: Robots and robotic devices - Safety requirements for industrial robots - Part 1: Robots.

- Refer to product catalogue, Operation Manual and Handling Precautions for SMC Products for additional information.
- Keep this manual in a safe place for future reference.

		Caution indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.
Warning indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury		
<b>Danger</b> Danger indicates a hazard with a high level of risk which, if not avoided, will result in death or serious injury.		

## A Warning

- Always ensure compliance with relevant safety laws and standards.
- All work must be carried out in a safe manner by a qualified person in compliance with applicable national regulations.

# 2 Specifications

This product is suitable for use in Zones 1, 2, 21 and 22 only.

# 2.1 Product Specifications:

Refer to the operation manual for this product;

# 2.1.1 Standard Product:

Fluid			Air	
Max. Operating Pressure			0.7 MPa	
Min. Operati	ng Pressure		0.05 MPa	
Ambient & Fluid Temperature			+5°C to +60°C	
Lubrication			Not Required	
Operating Piston Speed			50 to 500 mm/s	
Cushion			Rubber Bumper	
	Male Rod	Ø 20	0.11 J	
		Ø 25	0.18 J	
Allowable		Ø 32	0.29 J	
Kinetic		Ø 40	0.52 J	
Energy		Ø 20	0.11 J	
Lifergy	Female Rod	Ø 25	0.18 J	
		Ø 32	0.18 J	
		Ø 40	0.52 J	

#### 2.2 Production Batch Code:

The batch code printed on the label indicates the month and the year of production as per the following table;

Production Batch Codes								
/	Year	2021	2022	2023	 2027	2028	2029	
Month	<u> </u>	Z	А	В	 F	G	Н	
Jan	0	Zo	Ao	Bo	 Fo	Go	Ho	
Feb	Р	ZP	AP	BP	 FP	GP	HP	
Mar	Q	ZQ	AQ	BQ	 FQ	GQ	HQ	
Apr	R	ZR	AR	BR	 FR	GR	HR	
May	S	ZS	AS	BS	 FS	GS	HS	
Jun	Т	ZT	AT	BT	 FT	GT	HT	
Jul	U	ZU	AU	BU	 FU	GU	HU	
Aug	V	ZV	AV	BV	 FV	GV	ΗV	
Sep	W	ZW	AW	BW	 FW	GW	HW	
Oct	Х	ZX	AX	BX	 FX	GX	HX	
Nov	У	Zy	Ay	Ву	 Fy	Gy	Hy	
Dec	Ζ	ZZ	AZ	ΒZ	 FZ	GZ	ΗZ	

#### 2.3 Special Conditions of Use:

- Products are suitable for sub-divisions IIC & IIIC.
- Products are suitable for Zones 1, 2, 21 & 22 only.

# 2.3.1 Temperature Marking:

#### 2.3.1.1 Standard Product:

- In the normal ambient temperature range (+5°C to +40°C) the product is rated to temperature class T5 and has a maximum surface temperature of 99°C.
- In the special ambient temperature range (+40°C to +60°C) the product is rated to temperature class T4 and has a maximum surface temperature of 119°C.

# 3 Installation

#### 3.1 Installation

#### Warning

- Do not install the product unless the safety instructions have been read and understood.
- Do not twist or bend the cylinder, or mount the product when subject to tension.
- Do not use in an application where the product is stopped mid-stroke, via an external stop.
- Do not use where cylinders are being synchronised to move a single load.
- In order to install the product, use one of the brackets available found in the standard product catalogue;

#### **3 Installation (continued)**

Mounting Bracket [Part Number]	Sketch	Mounting Bracket [Part Number]	Sketch
Axial Foot [JCM-L***]		Flange [JCM-F***]	
(1-pc Foot & 1-pc Mounting Nut)		(1-pc Flange & 1-pc Mounting Nut)	- CE
^Related Mounting Bracket Option (L)		^Related Mounting Bracket Op	tion (F, FZ & G)
Rod End Nut [Ø20 = NT-02] [Ø25/Ø32 = NT-03] [Ø40 = NT-04]	Ø	Mounting Nut [Ø20 = JSN-020B] [Ø25/Ø32 = JSN-032B] [Ø40 = JSN-040B]	Ø

Note: The "\*" represents the Bore Size in three digits (e.g. Ø20 is 020), see catalogue for more details.

Rod End Accessories	Sketch	Series
Lightweight Floating Joint		JT

**Note 3:** See the product catalogue for the exact code to order which relates to the bore size of your product.

• Tighten these accessories with a suitable wrench using the flat surfaces provided. Ensure that they are tightened against the rod end nut to prevent the accessory coming loose during operation.

Dere [mm]	Width Across Flats [mm]
Bore [mm]	Floating Joint
Ø 20	13
Ø 25 & Ø 32	17
Ø 40	22

#### 3.2 Environment

- A Warning
- Do not use in an environment where corrosive gases, chemicals, salt water or steam are present.
- Do not use in an explosive atmosphere except within the specified


#### rating

- Do not expose to direct sunlight. Use a suitable protective cover.
- Do not install in a location subject to vibration or impact in excess of the product's specifications.
- Do not mount in a location exposed to radiant heat that would result in temperatures in excess of the product's specifications.
- Do not use in a place subject to heavy vibration and/or shock.
- Do not use in wet environments, where water can remove the presence of the lubrication.
- Do not use in case of heavy dusty environments where dust can penetrate into the cylinder and dry the grease.
- Do not allow dust layers to build up on the cylinder surface and insulate the product.

#### 3.3 Piping

#### **A** Caution

- Before connecting piping make sure to clean up chips, cutting oil, dust etc.
- When installing piping or fittings, ensure sealant material does not enter inside the port. When using seal tape, leave 1 thread exposed on the end of the pipe/fitting.
- Tighten fittings to the specified tightening torque.




# **3 Installation (continued)**

#### 3.4 Lubrication

# **Caution**

- SMC products have been lubricated for life at manufacture, and do not require lubrication in service.
- If a lubricant is used in the system, refer to catalogue for details.

#### 3.5 Basic Circuit



• Plugging one of the ports on the actuator is considered a non-intended use, and could relate to an increase in maximum surface temperature above what the product specification declares.

#### 3.6 Electrical Connection

- The product should be grounded by the piston rod and the body in order to create an electrically conductive path to the system/application.
- Ground the product in accordance with applicable regulations.
- Do not pass an electrical current through the product.

#### 4 Settings

Refer to the standard product catalogue for general setup precautions. **5 How to Order** 

Refer to the product catalogue for 'How to Order'.

#### 6 Outline Dimensions

# Refer to the standard product catalogue for general dimensions.

# 7 Maintenance

7.1 General maintenance

## **Caution**

- Not following proper maintenance procedures could cause the product to malfunction and lead to equipment damage.
- If handled improperly, compressed air can be dangerous.
- Maintenance of pneumatic systems should be performed only by qualified personnel.
- Before performing maintenance, turn off the power supply and be sure to cut off the supply pressure. Confirm that the air is released to atmosphere.
- After installation and maintenance, apply operating pressure and power to the equipment and perform appropriate functional and leakage tests to make sure the equipment is installed correctly.
- If any electrical connections are disturbed during maintenance, ensure they are reconnected correctly and safety checks are carried out as required to ensure continued compliance with applicable national regulations.
- Do not make any modification to the product.
- Do not disassemble the product, unless required by installation or maintenance instructions.
- Do not use a product which looks or contains damage, this will invalidate the certification. If damage is seen, please replace the product immediately.
- Periodically check the product for any damage or rust appearing. This could result in an increase in friction and lead to dangerous conditions. Replace the whole actuator if any of these conditions appear.
- Replace the product, when air leakage is above the allowable value given in the table below;

	Allowable Leakage
Internal Leakage	10 cm <sup>3</sup> / min (ANR)
External Leakage	5 cm <sup>3</sup> / min (ANR)

#### 8 Limitations of Use

**8.1 Limited warranty and disclaimer/compliance requirements** Refer to Handling Precautions for SMC Products.

# Caution

- 8.2 Obligations of the end-user
- Ensure the product is used within the specification outlined.
- Ensure that the maintenance periods are suitable for the application.
- Ensure any cleaning processes to remove dust layers are made with the atmosphere in mind (e.g. using a damp cloth to avoid static build up).
- Ensure that the application does not introduce additional hazards by mounting, loading, impacts or other methods.
- Ensure that there is sufficient ventilation and air circulation around the product.
- If the product is subject to direct heat sources in the application, they should be shielded so that the actuator temperature stays within the stated operating range.

#### **Danger**

- Do not exceed any of the specifications listed in Section 2 of this document as this will be deemed improper use.
- Air equipment has an air leakage during operation within certain limits. Do not use this equipment when the air itself introduces additional hazards and could lead to an explosion.
- Use only Ex certified auto switches. These should be ordered separately.
- Do not use this product in the presence of strong magnetic fields that could generate a surface temperature higher than the product specification.
- Avoid applications where the piston rod end and the adjoining part in the application can create a possible ignition source.
- Do not install or use these actuators where there is the possibility for the piston rod to impact foreign objects.
- In the event of damage or failure of any parts located in the vicinity

where this product has been installed, it is the responsibility of the user to determine whether or not this has compromised the safety and condition of this product and/or the application.

- External impact on the cylinder body could result in a spark and/or cylinder damage. Avoid any application where foreign objects can hit or impact the cylinder. In such situations the application should install a suitable guard to prevent this occurrence.
- Do not use this equipment where vibration could lead to failure.

#### 9 Product Disposal

This product shall not be disposed of as municipal waste. Check your local regulations and guidelines to dispose this product correctly, in order to reduce the impact on human health and the environment.

#### **10 Contacts**

Refer to <u>www.smcworld.com</u> or <u>www.smc.eu</u> for your local distributor/importer.

# **SMC** Corporation

URL: https:// www.smcworld.com (Global) https:// www.smc.eu (Europe) SMC Corporation, 4-14-1, Sotokanda, Chiyoda-ku, Tokyo 101-0021, Japan Specifications are subject to change without prior notice from the manufacturer. © 2022 SMC Corporation All Rights Reserved. Template DKP50047-F-085M