Air Cylinder/Non-rotating Rod Type: Double Acting, Single Rod

CA2K Series

ø40, ø50, ø63



Actuators

Rotary Actuators Air Grippers


Equipment Control E


Modular F.R.L Pressure (

Air Preparation Equipment


ndustrial Filters

Construction





* The numbers correspond with those in the "Construction" of the CA2K series in the Web Catalog.



Seal Kit List

to be replaced.

Description	Material	Note		
Cushion seal	Urethane			
Rod seal	NBR	21 is a non-replaceable part, so it is not included in the seal kit.		
Piston seal	NBR			
Cushion valve seal	NBR			
Cylinder tube gasket	NBR			
	Cushion seal Rod seal Piston seal Cushion valve seal	Cushion sealUrethaneRod sealNBRPiston sealNBRCushion valve sealNBR		

Disassembly/Replacement

1. Please consult with SMC when the rod seal is to be replaced.

When the rod seal is to be replaced, make sure that the seal's width across flats matches that of the non-rotating guide. A rod seal may allow air leakage depending on the position where it is installed. Therefore, please consult with SMC when a rod seal is

Do not replace the non-rotating guide.

Since the non-rotating guide is press fitted, the entire cover assembly needs be replaced instead of a single part.

For details on replacement part numbers, refer to page 248.

Replacement Parts: Seal Kit

* Replaceable with the rod boot assembly

Bore size (mm)	Part no.	Contents
40	CA2K40-PS	Ostatura
50	CA2K50-PS	Set of nos. (18, (19, 20, 22)
63	CA2K63-PS	(0, (3, 20, 22

* The seal kit includes (18, (19, 20) and 22). Order the seal kit based on each bore size.

* Do not disassemble the trunnion type.

* The seal kit includes a grease pack (ø40, ø50: 10 g, over ø63: 20 g). Order with one of the following part numbers when only the grease pack is required

Grease pack part no.: GR-S-010 (10 g), GR-S-020 (20 g)

Actuators

@SMC