Contact our sales office regarding a delivery date or price since this is a special model.

SNC. P.G. Information (Specialized Product)

SP145X-006E P SS

Flow sensor

PFMV505-1-X502

SMC Corporation 4-14-1, SOTO-KANDA CHIYODA-KU Tokyo, 101-0021, JAPAN URL: http://www.smcworld.com

- Features
 Flow range: 0 to 0.1 L/min
 - •Compatible with voltage monitor, PFMV3
 - (displays voltage only)
- Application
 - •Easily detects leakage rate





Specifications

Product Specifications

Froduct Specifications	
Applicable fluid	Dry air, N ₂ (Air quality grade is JIS B 8392-1 1.1.2 to 1.6.2: 2003, ISO 8573-1 1.1.2 to 1.6.2)
Rated flow range ^{Note1)} Flow rate range	0 to 0.1 L/min
Repeatability	±3% F.S. ^{Note2})
Pressure characteristics (0kPa ^{Note3)})	±3% F.S. (0 to 300 kPa) ±7% F.S. (-70 to 0 kPa)
Rated pressure range Note4)	-70 kPa to 300 kPa
Proof pressure	500 kPa
Analog output (Non-linear output)	Voltage output: 1 to 5 V, Output impedance: Approx. 1 $k\Omega$
Response time	5 ms or less (90% response)
Power supply voltage	DC12 to 24 V ±10%, Ripple (p-p) 10% or less
Current consumption	It should be 16 mA or less
Enclosure	IP40
Mounting	Horizontal Note6)
fluid temperature	0 to 50 °C (No freezing or condensation)
Wetted material	PPS, Si, Au, SUS316, C3604 (electroless nickel plating)
Lead wire	Heavy-duty vinyl cable, 3 cores ø2.6, 0.15mm ² , 2m
Weight	10 g (without lead wire)

Note: 1. Volume flow converted value under standard conditions: 20 degrees °C, 101.3kPa, 65%R.H.

- 2. The unit % F.S. is based on the full scale of analog 4V (1-5V)
- 3. 0 kPa indicates the atmospheric release
- 4. Pressure range that satisfies the product specifications
- 5. Caution: If pressure is rapidly supplied to inlet side, this could cause an overflow in the piping and damage the product.
- 6. Please use this special product for horizontal mounting (vertical mounting is not guaranteed)
- 7. For details, please refer to the Operation Manual (PF**-OMK0003) for Standard products (PFMV5 series)

Circuit diagram



Dimensions (mm)





View A

Caution: To ensure the safest possible operation of this product, please be sure to thoroughly read the "Safety Instructions" in our "Best Pneumatics" catalog before use.